

# ステンレス鋼(マルテンサイト系)

丸棒：サイズ単位(mm)

鋼種 サイズ	SUS403	SUS420J2	SUS440C
10	●		
13	●	●	
16	●	●	
18	○	○	
19	○	○	○
20	○	○	○
22	○	○	○
24	○	○	
25	○	○	○
26	○	○	○
28	○	○	○
30	○	○	○
32	○	○	○
34	○	○	○
35	○	○	
36	○	○	○
38	○	○	○
40	○	○	○
42	○	○	○
44	○	○	
45	○	○	○
46	○	○	○
48	○	○	
50	○	○	○
55	○	○	○
60	○	○	○
65	○	○	○
70	○	○	○
75	○	○	○
80	○	○	○
85	○	○	○
90	○	○	○
95	○	○	○
100	○	○	○
105			
110	○	○	○
115			
120	○	○	○
125			
130	○	○	○
135			
140	○	○	○
145			
150	○	○	○

(注) ●:酸洗肌 ○:ピーリング、ターニング

鋼種 サイズ	SUS403	SUS420J2	SUS440C
160	○	○	○
170	○	○	○
180	○	○	○
190	○	○	
200	○	○	○
210	○	○	
220	○	○	
230	○	○	
240	○	○	
250	○	○	
260	○	○	
270	○	○	
280	○	○	
290	○	○	
300	○	○	
310	○		
320	○		
330			
340			
350	○	○	
360			
370			
380			
390			
400	○		
410			
420			
430			
440			
443			
450	○		
460			
465			
470			
480			
485			

<仕様> すべてA品(焼鈍)

## ステンレス鋼(オーステナイト系①)

丸棒：サイズ単位(mm)

鋼種 サイズ	SUS304	SUS303	SUS316
10			
13	●		●
16	○	○	○
18	○	○	○
19	○	○	○
20	○	○	○
22	○	○	○
24	○	○	○
25	○	○	○
26	○	○	○
28	○	○	○
30	○	○	○
32	○	○	○
34	○	○	○
35	○	○	○
36	○	○	○
38	○	○	○
40	○	○	○
42	○	○	○
44	○	○	○
45	○	○	○
46	○	○	○
48	○	○	○
50	○	○	○
55	○	○	○
60	○	○	○
65	○	○	○
70	○	○	○
75	○	○	○
80	○	○	○
85	○	○	○
90	○	○	○
95	○	○	○
100	○	○	○
105	○		
110	○	○	○
115	○		
120	○	○	○
125	○		
130	○	○	○
135	○		
140	○	○	○
145	○		○
150	○	○	○

(注) ●:酸洗肌 ○:ピーリング、ターニング

鋼種 サイズ	SUS304	SUS303	SUS316
160	○	○	○
170	○	○	○
180	○	○	○
190	○	○	○
200	○	○	○
210	○	○	○
220	○	○	○
230	○	○	○
240	○	○	○
250	○	○	○
260	○	○	○
270	○	○	○
280	○	○	○
290	○	○	○
300	○	○	○
310	○		
320	○		○
330	○		
340	○		
350	○		
360	○		
370	○		
380	○		
390	○		
400	○		
410			
420	○		
430			
440			
450			
460			
470			
480			

<仕様> すべてST品(固溶化熱処理)

## ステンレス鋼(オーステナイト系②)

丸棒：サイズ単位(mm)

鋼種 サイズ	SUS304L	SUS316L	SUS304N2
10			
13			
16			○
18			
19	○	○	
20		○	
22	○	○	
24			
25	○	○	
26			
28	○	○	○
30	○	○	
32	○	○	○
34			
35		○	
36	○	○	
38		○	
40	○	○	○
42		○	
44			
45	○	○	○
46		○	
48			
50	○	○	○
55	○	○	○
60	○	○	○
65	○	○	○
70	○	○	○
75	○	○	
80	○	○	
85	○	○	○
90	○	○	○
95			
100	○	○	○
105			
110	○	○	
115			
120	○	○	
125			
130	○	○	○
135			
140	○	○	
145			
150	○	○	○

(注) ○:ピーリング、ターニング

鋼種 サイズ	SUS304L	SUS316L	SUS304N2
160	○	○	
170		○	
180	○	○	
190		○	
200	○	○	
210		○	
220		○	
230		○	
240		○	
250		○	
260		○	
270			
280			
290			
300			
310			
320			
330			
340			
350			
360			
370			
380			
390			
400			
410			
420			
430			
440			
450			
460			
470			
480			

〈仕様〉 すべてST品(固溶化熱処理)

## ステンレス鋼(析出硬化系)

丸棒：サイズ単位(mm)

鋼種 サイズ	SUS630
10	●
13	●
16	○
18	
19	○
20	○
22	○
24	
25	○
26	○
28	○
30	○
32	○
34	○
35	
36	○
38	○
40	○
42	○
44	
45	○
46	○
48	
50	○
55	○
60	○
65	○
70	○
75	○
80	○
85	○
90	○
95	○
100	○
105	
110	○
115	
120	○
125	
130	○
135	
140	○
145	
150	○

(注) ●：酸洗肌 ○：ピーリング、ターニング

鋼種 サイズ	SUS630
160	○
170	○
180	○
190	○
200	○
210	○
220	○
230	○
240	○
250	○
260	
270	
280	
290	
300	○
310	
320	
330	
340	
350	○
360	
370	
380	
390	
400	
410	
420	
430	
440	
450	
460	
470	
480	

〈仕様〉 すべてST品(固溶化熱処理)

# ステンレス鋼(ビレット・鍛造用)

丸棒：サイズ単位(mm)

鋼種 サイズ	SUS304	SUS304L	SUS316	SUS316L
10				
13				
16				
18				
19				
20				
22				
24				
25	○			
26			○	
28	○		○	
30			○	
32	○			
34	○		○	
35				
36	○		○	
38	○		○	
40	○		○	
42	○			○
44				
45				
46	○			
48				
50	○		○	○
55	○		○	○
60	○		○	○
65	○			
70	○		○	○
75	○		○	
80	○		○	○
85			○	
90	○		○	○
95			○	
100	○	○	○	○
105				
110	○			○
115				
120	○		○	
125				
130	○		○	○
135				
140	○			
145				
150	○	○	○	○

(注) ○:ピーリング、ターニング

鋼種 サイズ	SUS304	SUS304L	SUS316	SUS316L
160				
170				
180				
190				
200	○	○	○	○
210				
220				
230				
240				
250	○	○	○	○
260				
270				
280				
290				
300	○	○	○	○
310				
320				
330				
340				
350	○	○	○	○
360				
370				
380				
390				
400	○	○	○	○
410				
420				
430				
440				
450	○		○	
460				
470				
480				

〈仕様〉 すべてR品(圧延のままas-rolled)